



TECHNICAL DATA SHEET- PRODUCT CODE S707

SUPERSPRAY ADHESIVE

DESCRIPTION

Superspray Adhesive is general purpose DCM free aerosol adhesive.

USES

It has been designed for the fixing of Carpet Tiles, Foam Backed Carpets, Polyurethane-Backed Carpets, Foam and Paper Underlays, Felts, Textiles and Fabrics to Wood Stone, Tiles, Concrete, Plaster and Brickwork. **Not suitable for expanded polystyrene, Vinyls & Linoleum. For Vinyls & Linoleum, use Stikatak Vinyl Spray Adhesive (S730). Not suitable for conditions where temperatures exceed 50°C**

STORAGE

Superspray Adhesive must be stored at a moderate temperature. Keep container in a well ventilated area and away from sources of ignition.

APPLICATION

- Surfaces to be joined must be free from dust and grease.
- Shake can before use, spray approx. 15 -20cm (6-8 inches) from one or both surfaces.
- One- way system – Spray one surface, leave to dry for 1 minute until tacky and press into position.
- Two- way system – sprays both surfaces and allow to dry for 2-5 minutes before bonding (Always invert can and spray to clear nozzle).

COVERAGE

3 – 4 m² per 500ml can.

WARNING

Do not ingest. Avoid skin contact. Use in well ventilated areas. In case of accident wash eyes and sensitive skin with clean cold water. If irritation persists take medical advice. Keep away from children and pets. Do not empty into drains.

PRECAUTIONS

- Extremely Flammable
- Keep away from sources of ignition
- No Smoking
- In case of poor ventilation use suitable respiratory equipment
- Pressurised container – Protect from sunlight and do not expose to temperatures greater than 50°C
- Do not pierce or burn even after use
- Do not spray on naked flame or any incandescent material

PROPERTIES

Colour	Pale Straw
Consistency	Aerosol Spray
Specific Gravity	0.7
Shelf life	12 Months if stored between 5-25°C in a cool dry area

REMOVAL OF ADHESIVE

Misdirected spray may be cleaned with White Spirits

GUARANTEE

STIKATAK LTD will guarantee the performance and quality of products against manufacturing defects provided they are used in accordance with our relevant Technical Data Sheets at the time of installation and the appropriate subfloor preparation has been undertaken in accordance with the relevant British Standards.

Floorcovering Manufacturers are constantly introducing new backings and improving their current products. Certain backings may have unique characteristics, which may influence the choice of adhesive used.

Whilst every effort has been made to ensure the information is correct at the time of publication it is the responsibility of the user to ensure that the product is suitable for the particular installation. If there is any doubt as to the use of our adhesives the installer should contact the Stikatak Technical Department for advice or carry out their own tests to ensure compatibility.

IMPORTANT NOTE

The information contained in this Data Sheet is based on tests believed to be reliable, practical experience and is published in good faith. However because we have no control over the application conditions we do not guarantee the results obtained. Responsibility for establishing suitability of the product rests with the purchaser. No liability or claim for damage or consequential loss is accepted from the use of this product.

Unit J, Braintree Road Industrial Estate, Braintree Road, Ruislip,
Middlesex HA4 OEG
Telephone : +44 (0) 208 – 839 4405 Facsimile : +44 (0) 208 842 1387